KELVIN DOUBLE BRIDGE DCB-KDB01





MOST OF OUR PRACTICAL BRIDGES ARE NOW MANUFACTURED IN THEORETICAL WAYS. FOR EASY UNDERSTANDING ABOUT THE CIRCUIT PERFORMANCES, THE FRONT PANEL OF THE KITS ARE DESIGNED LIKE THE ACTUAL THEORETICAL BRIDGE DIAGRAM. CURRENT CIRCUIT IS ALSO INCORPORATED WITHIN THIS KIT, TO SAVE SPACE & MONEY. THERE IS NO NEED OF EXTERNAL NULL INDICATOR FOR BALANCE AS THIS KIT IS PROVIDED WITH IN-BUILT DIGITAL HIGH I,PIDANCE NULL INDICATOR. DUE TO THIS HI WATT WW POTS ARE USED IN VITAL NULL ADJUSTMENT ARM. INBUILT LOW RESISTANCE BED WITH 4 POINT MEASUREMENT FACILITY PROVIDED.

** MODELS: DCB-KDB01

THIS KIT CONSISTS OF:-

- ACTUAL BRIDGE DIAGRAM WISE COMPONENTS.
- > WIRE WOUND HI WATT POT/S IN VITAL BRIDGE ARM/S.
- > INBUILT 0-10 AMP DC CURRENT SOURCE.
- DIGITAL NULL INDICATOR.
- BUILT IN AUDIO AMPLIFIER & SPEAKER INBUILT FOR AUDIO NULL ADJUST MODE.
- INBUILT LOW RESISTANCE BED WITH 4 POINT MEASUREMENT FACILITY PROVIDED.
- WOODEN & BACKLIT HARD CABINET FOR LONG LIFE USE.
- DIMENSION: 24"X10"X8"

MFD. BY:-

PODDAR SYSTEM & SERVICES, 57/8/1, SANTOSH ROY ROAD,

KOLKATA - 700008.

PH: 033-24947123/09433012210 EMAIL: SOSPODDARAV@HOTMAIL.COM

AD 590 TEMPERATURE SENSOR STUDY SETUP



MODEL: TAD5901